


TORRO® WF



Long-lasting automatic re-tensioning effect

- ✓ Automatic re-tensioning effect in the event of hose relaxation
- ✓ Increased sealing reliability across a wide temperature range
- ✓ Multi-range hose clamp
- ✓ Improved asymmetric housing: even distribution of forces and safe assembly



Applications

TORRO® WF the optimal solution for applications under extreme temperature changes (e.g. charged air, cooling water lines, depressurized and pressurized fuel lines and ventilation systems, oil lines and a wide variety of industrial applications).

Material

Group	W3, W4
Band & housing	W3 (SS – AISI 430), W4 (SS – AISI 304)
Screw	W3 (SS – AISI 403), W4 (SS – AISI 304)

Additional sizes and materials might be available on request. Please get in touch with us!

Description	Band Width (mm)	Clamping Range Ø NW (mm)	Part Number		Packaging Quantity (pcs)
			W3	W4	
TORRO® WF 10-16	9	10 – 16	0127 7708 013	0127 7711 013	100
TORRO® WF 12-22	9	12 – 22	0127 7708 017	0127 7711 017	100
TORRO® WF 16-27	9	16 – 27	0127 7708 021	0127 7711 021	100
TORRO® WF 20-32	9	20 – 32	0127 7708 026	0127 7711 026	100
TORRO® WF 23-35	9	23 – 35	0127 7708 029	0127 7711 029	100
TORRO® WF 25-40	9	25 – 40	0127 7708 032	0127 7711 032	100
TORRO® WF 30-45	9	30 – 45	0127 7708 037	0127 7711 037	100
TORRO® WF 32-50	9	32 – 50	0127 7708 041	0127 7711 041	50
TORRO® WF 40-60	9	40 – 60	0127 7708 050	0127 7711 050	50
TORRO® WF 50-70	9	50 – 70	0127 7708 060	0127 7711 060	50
TORRO® WF 60-80	9	60 – 80	0127 7708 070	0127 7711 070	25
TORRO® WF 70-90	9	70 – 90	0127 7708 080	0127 7711 080	25
TORRO® WF 80-100	9	80 – 100	0127 7708 090	0127 7711 090	25
TORRO® WF 90-110	9	90 – 110	0127 7708 100	0127 7711 100	25
TORRO® WF 16-27	12	16 – 27	0137 7708 021	0137 7711 021	50
TORRO® WF 20-32	12	20 – 32	0137 7708 026	0137 7711 026	50
TORRO® WF 25-40	12	25 – 40	0137 7708 032	0137 7711 032	50
TORRO® WF 30-45	12	30 – 45	0137 7708 037	0137 7711 037	50
TORRO® WF 35-50	12	35 – 50	0137 7708 043	0137 7711 043	50
TORRO® WF 40-60	12	40 – 60	0137 7708 050	0137 7711 050	25
TORRO® WF 50-70	12	50 – 70	0137 7708 060	0137 7711 060	25
TORRO® WF 60-80	12	60 – 80	0137 7708 070	0137 7711 070	25
TORRO® WF 70-90	12	70 – 90	0137 7708 080	0137 7711 080	25
TORRO® WF 80-100	12	80 – 100	0137 7708 090	0137 7711 090	20
TORRO® WF 90-110	12	90 – 110	0137 7708 100	0137 7711 100	20

Technical Benefits

- ✓ No chromium (VI) used for coating purposes
- ✓ Material and clamping range stamped on the band – prevention of errors
- ✓ Asymmetric extension – prevents the housing from tilting over when the clamp is tightened
- ✓ Short housing saddle, even contact pressure
- ✓ Smooth or stamped inside of band for optimal hose protection

The TORRO® WF is part of our broad portfolio. Discover more hose fasteners and other products on our new Mobility website: mobility.normagroup.com



Do you have questions or require a personal consultation?
 Feel free to contact our NORMA Team!
 Visit our website for more information about our products: mobility.normagroup.com